



HOLLISTER-WHITNEY ELEVATOR CORPORATION

#1 Hollister-Whitney Parkway
 Quincy, IL 62305
 Phone: 217-222-0466

Fax: 217-222-0493
 email: engineering@hollisterwhitney.com
www.hollisterwhitney.com

HOLLISTER-WHITNEY VVVF LOW-SLIP HOIST MOTOR DATA TOTALLY ENCLOSED

	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	1200 SRPM VERSION	5	208 / 230 / 460	-	215T	1150	17.3 / 15.6 / 7.8
7-1/2		208 / 230 / 460	3200	254T	1175	24.1 / 21.8 / 10.9	195
10		208 / 230 / 460	4000	256T	1176	31.6 / 28.6 / 14.3	225
12-1/2		208 / 230 / 460	5170	284T	1160	44.2 / 40 / 20	195
15		208 / 230 / 460	5170	284T	1160	46.4 / 42 / 21	240
20		208 / 230 / 460	6230	286T	1160	59.7 / 54 / 27	285
25		208 / 230 / 460	7360	324T	1170	75.2 / 68 / 34	375
30		208 / 230 / 460	8480	326T	1170	87.4 / 79 / 39.5	410
40		208 / 230 / 460	11610	364T	1180	103.9 / 94 / 47	485
50		208 / 230 / 460	13920	365T	1180	130.5 / 118 / 59	515
60		208 / 230 / 460	15700	L365T	1180	154.8 / 140 / 70	560
75	208 / 230 / 460	18570	L365T	1180	192.4 / 174 / 87	675	
900 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208 / 230 / 460	-	254T	876	22.3 / 20.2 / 10.1	225
	7-1/2	208 / 230 / 460	3200	256T	876	30.3 / 27.4 / 13.7	200
	10	208 / 230 / 460	4000	284T	876	34.3 / 31.0 / 15.5	300
	12-1/2	208 / 230 / 460	5170	-	876	46.4 / 42 / 21	-
	15	208 / 230 / 460	5170	286T	876	55.5 / 50.2 / 25.1	320
	20	208 / 230 / 460	6230	324T	876	-	340
	25	208 / 230 / 460	7360	326T	876	85.1 / 77 / 38.5	570
	30	208 / 230 / 460	8480	364T	876	88.5 / 80 / 40	700
	40	208 / 230 / 460	11610	365T	876	116.3 / 105.2 / 52.6	880
	50	208 / 230 / 460	13920	404T	876	148 / 134 / 67	-
60	208 / 230 / 460	15700	405T	876	179 / 162 / 81	-	
75	208 / 230 / 460	18570	444T	876	215 / 194 / 97	-	
1800 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	10	208 / 230 / 460	4000	215T	1764	28 / 26 / 13	160
	15	208 / 230 / 460	5170	254T	1764	-	180
	20	208 / 230 / 460	6230	256T	1764	51.5 / 46.6 / 23.3	175
	25	208 / 230 / 460	7360	284T	1764	68.6 / 62.0 / 31.0	260
	30	208 / 230 / 460	8480	286T	1764	-	340
	40	208 / 230 / 460	11610	324T	1764	107.7 / 92.0 / 46.0	500
	50	208 / 230 / 460	13920	326T	1764	130.5 / 118 / 59	475
60	208 / 230 / 460	15700	364T	1764	154.1 / 139.4 / 69.7	680	
75	208 / 230 / 460	18570	365T	1764	186.9 / 169 / 84.5	840	

Totally Enclosed, Non-vent motors by REULAND
 All Models have 35 foot Encoder Cables
 Standard Encoder is 2048 PPR; also available in 1024 PPR
 Constant Torque 0-60 Hz
 Variable Torque 60-90 Hz
 60 Minute Duty - Inverter Duty
 Extended End Play
 Foot Mount Motors