


(SW21-1000L)




(SW21-1000L)




AT INITIAL SET-UP ADJUST THE POSITION OF THE ZONE CAM AND THE ROLLER ARM WITH THE DOORS FULLY CLOSED SO THAT THE ROLLER IS 1/16" FROM THE ZONE CAM AS SHOWN. LOCK THE ROLLER ARM AND ZONE CAM SECURELY IN PLACE TO MAINTAIN THIS CLEARANCE.


FOR SET-UP AT ALL SUBSEQUENT LANDINGS, ADJUST THE POSITION OF THE ZONE CAM ONLY, WITH THE DOORS FULLY CLOSED, TO ESTABLISH THE SAME 1/16" CLEARANCE BETWEEN THE ROLLER AND ZONE CAM. LOCK THE ZONE CAM SECURELY IN PLACE TO MAINTAIN THIS CLEARANCE.


\* SET-UP IS IDENTICAL FOR ALL DOOR SPEEDS.




DETAIL C









TYPE "SN-Z" LOCK AND ELECTRIC CONTACT

UNLESS OTHERWISE SPECIFIED DIMENTIONS ARE IN INCHES .... (X.)

G.A.L. MANUFACTURING CORP.
50 East 153rd St. Bronx, NY 10451 (718)292-9000
PA

THE DAY WING AND THE DESIGNS CONTAINED BY THE PROPERTY OF SALL MANUFACTURING CORP.

THE DAY WING AND THE DESIGNS CONTAINED BY THE PROPERTY OF SALL MANUFACTURING CORP.

THE DAY WING AND THE DESIGNS CONTAINED BY THE PROPERTY OF SALL MANUFACTURING CORP.

8715-10

DRAWING: 8715-10.idw

AWING: 8715-10.idw MODEL: SW21-1000L.iam "SN-Z" LOCK AND ELECTRIC CONTACT

 1
 1
 INT5-0025N
 ARM & ROLLER, 4 1/2" CL

 2
 2
 HWBS-0012N
 BUSHING, TYPE 7 SNAP IN NYLINER 7/16" ID

 3
 1
 INT22-0022N
 CONTACT ASSEMBLY, N/NHA INTERLOCK LOWER

 4
 1
 SHF-0199N
 SHAFT, 6 INCH "SN-Z"

 5
 1
 SPG-0030N
 SPRING,1 7/8" LG x 13/32" OD-0.050 WIRE

 6
 1
 SW21-9001N
 COVER ASSEMBLY

 7
 1
 ZLK1-0004L/R
 ASSEMBLY, SN-Z CAR DOOR LOCKING CAM

 8
 1
 SW21-9005N
 "SN-Z" MOUNTING BRACKET

SW21-9006L/R KEEPER, SN-Z ZONE LOCK CAR DOOR

SELECT REPLACEMENT PARTS LIST

DESCRIPTION

ITEM QTY PART NUMBER