



- WARNING -  
 G.A.L. PROPRIETARY INFORMATION  
 REPRODUCTION AND/OR USE OF ALL OR ANY  
 PART OF THIS (THESE) PAGE(S) OR DRAWING(S)  
 OR THE INFORMATION HEREIN, WITHOUT THE  
 EXPRESS PERMISSION OF G.A.L. MANUFACTURING  
 CORPORATION IS STRICTLY PROHIBITED BY LAW.  
 - VIOLATORS WILL BE PROSECUTED -

69-72	106	10	3	26 1/2	35	19
65-68	100	9	5	24 1/2	31	19
61-64	94	9	2	22 1/2	31	17
57-60	88	8	4	20 1/2	27	17
53-56	82	7	6	18 1/2	27	15
49-52	76	7	3	16 1/2	23	15
47-48	72	6	6	16 1/2	23	13
45-46	70	6	5	16 1/2	23	13
43-44	66	6	3	14 1/2	19	13
41-42	64	6	2	14 1/2	19	13
39-40	60	5	5	12 1/2	$\frac{(40)}{(39)} \frac{19}{15}$	13
37-38	58	5	4	12 1/2	15	13
35-36	54	5	2	10 1/2	15	13
33-34	52	4	6	10 1/2	15	13
31-32	48	4	4	8 1/2	15	13
30	46	4	3	8 1/2	15	13
DOOR OPNG.	A	B	C	D	M	N
DIMENSION TABLE						

NOTES :

- CLUTCH, PENDANT BOLT AND HEADER HANGER SUPPORT DRILLINGS LOCATED FROM DAYLITE, REGARDLESS OF DOOR LAP SIZE. G.A.L. PREFERS 1 1/4 LAP AT THE LEADING EDGE ONLY.
- DRAWINGS ARE BASED ON EQUAL CAR AND HOISTWAY DOOR HEIGHTS ±1 INCH. IF DOOR HEIGHTS DIFFER NOTIFY G.A.L. AND HOISTWAY DOOR MFG'R.

\* REQUIRED ONLY IF ELECTRIC EYES BY G.A.L.  
 (36 x 84 D.O. SHOWN)

AS SHOWN L.H. \_\_\_\_\_  
 SYMMETRICALLY \_\_\_\_\_  
 OPPOSITE R.H. \_\_\_\_\_  
 DOOR HEIGHT \_\_\_\_\_  
 JAMB HEIGHT \_\_\_\_\_



G.A.L. MANUFACTURING CORP.  
 50 E. 153rd STREET BRONX, N.Y. 10451

CAR REINFORCEMENT AND DRILLINGS TWO SPEED  
 TYPE "A" HANGER W/RAL SAFETY EDGE AND ELECTRIC EYES OR SCANGUARD 30-72 D.O.

SCALE	3/32	DATE	10-31-94
DWG. BY			
REV. No.			8232