



DIMENSION TABLE				
DOOR OPENING	A	B	C	D
46-47-48	94	24 (FIG. 3)	12	34
43-44-45	88	24 (FIG. 2)	24	31
40-41-42	82	24 (FIG. 2)	24	28
37-38-39	76	24 (FIG. 2)	12	25
34-35-36	70	24 (FIG. 2)	12	22
31-32-33	64	24 (FIG. 1)	-	19
28-29-30	58	24 (FIG. 1)	-	16
25-26-27	52	18 (FIG. 1)	-	13
22-23-24	46	18 (FIG. 1)	-	10

NOTES:

- PENDANT BOLTS AND HANGER DRILLINGS LOCATED FROM DAYLITE REGARDLESS OF DOOR LAP SIZE, G.A.L. PREFERRED 3/4 LAP.
- DRAWINGS ARE BASED ON EQUAL CAR AND HOISTWAY DOOR HEIGHTS ±1 INCH. IF DOOR HEIGHTS DIFFER, NOTIFY G.A.L. AND HOISTWAY DOOR MANUFACTURER.
- FOR PUSH BUTTON CONTROL (BROKEN ARM CLOSER) FLUSH CUP AND HANDLE REQUIRED ON DOOR.
- FOR CAR SWITCH CONTROL (STRAIGHT ARM CLOSER) FLUSH CUP AND HANDLE NOT REQUIRED.
- DOOR BUMPERS TO BE SUPPLIED BY OTHERS. NO OVERTRAVEL REQUIRED.

AS SHOWN R.H. _____

SYMMETRICALLY
OPPOSITE L.H. _____

DOOR HEIGHT _____

JAMB HEIGHT _____

LIMITED CLEARANCE BEHIND DOOR

FIGURE 1

- WARNING -

G.A.L. PROPRIETARY INFORMATION
REPRODUCTION AND/OR USE OF ALL OR ANY PART OF THIS (THESE) PAGE(S) OR DRAWING(S) OR THE INFORMATION HEREIN, WITHOUT THE EXPRESS PERMISSION OF G.A.L. MANUFACTURING CORPORATION IS STRICTLY PROHIBITED BY LAW.

- VIOLATORS WILL BE PROSECUTED -

REV	DESCRIPTION	DATE
D	DRAWING AND TEMPLATE UPDATE	05-21-14
C	ECN 221	01-09-73
B	ECN 152	11-09-66
A	DRAWING CREATED	05-16-58



HATCH REINFORCEMENT AND DRILLINGS SINGLE SPEED TYPE "A" HANGER MANUALLY OPERATED INSTALLATION 22-48 DOOR OPENING

G.A.L. MANUFACTURING CORP.
50 E. 153rd STREET, BRONX, N.Y. 10451
PHONE: (718) 292-9000, FAX: (718) 292-2034
www.GAL.com, info@GAL.com

DATE 07-16-2003

DOCUMENT No.

LT-5441

REV

D